

Flesher Corporation

507 Jackson • P.O. Box 976 • Topeka, Kansas 66601 •

T U - 3 0 0

A D D E N D A

=====

APRIL 20TH 1982

=====

CHANGE NO. 1

MANUAL EFFECTED: ASSEMBLY MANUAL

PAGE NO. 8

CHANGE FROM: (✓) R28: ~~220K~~ ohm (~~RED-RED-YEL~~)

CHANGE TO: (✓) R28: ~~300K~~ ohm (~~ORG-BLK-YEL~~)

=====

CHANGE NO. 2

MANUAL EFFECTED: OPERATORS MANUAL

PAGE NO. 27

CHANGE FROM: R28 ✓ ~~101 390~~ 220K ohm resistor 1/4 Watt 5% RED-RED-YEL

CHANGE TO: R28 ✓ 101 410 300K ohm resistor 1/4 Watt 5% ORG-BLK-YEL

=====

CHANGE NO. 3

MANUAL EFFECTED: OPERATORS MANUAL

PAGE NO. 34

CHANGE FROM: R1 ✓ ~~100 850~~ Resistor, 2.2M ohm, 1/4 watt, 5% RED-RED-GRN

CHANGE TO: R1 ✓ 101 600 Resistor, 2.2M ohm, 1/4 watt, 5% RED-RED-GRN

T U - 3 0 0

A D D E N D A

CHANGE NO. 5

MANUAL EFFECTED: UNIVERSAL FILTER ASSEMBLY

PAGE NO. 3

CHANGE FROM: (✓) P1 200 ohm potentiometer
(✓) P2 200 ohm potentiometer
(✓) P3 200 ohm potentiometer

CHANGE TO: (✓) P1 500 ohm potentiometer
(✓) P2 500 ohm potentiometer
(✓) P3 500 ohm potentiometer

=====

CHANGE NO. 6

MANUAL EFFECTED: DEMODULATOR BOARD ASSEMBLY

PAGE NO. 2

CHANGE FROM: (✓) R11: 2.2K ohm resistor (ORG-ORG-ORG)

CHANGE TO: (✓) R11: 2.2K ohm resistor (RED-RED-RED)

=====

CHANGE NO. 7

MANUAL EFFECTED: ASSEMBLY MANUAL

PAGE NO. 18 ✓

CHANGE: Each instruction on this page refers to an illustration on the opposite page which is in-correct. The correct location of these illustrations is the following page.