REGISTER NO.

A CONTRACTOR OF THE PARTY OF TH

0674 CSP 6620 (A) (Reg #1)

31-02

CRYPTO

CRYPTO

CRYPTOGRAPHIC EQUIPMENT PLANNING AND REFERENCE GUIDE (U)

CSP 6620A

DEPARTMENT OF THE NAVY
OFFICE OF THE CHIEF OF NAVAL OPERATIONS
SEPTEMBER 1962

DO NOT REMOVE FROM BINDER


TOWNS TOWN AUTOMATIC R 5200.10

DECLASSIFIED per SEC 3.4 E.O. 12958 by Director, NSA/Chief, CS3 date 270cfgg

CRYPTO

CSP 6620A UNCLASSIFIED AN/GGA-1 ORIGINAL UNCLASSIFIED 2-5

DESCRIPTION	THE AN/GGA-1 SEMI-AUTOMATIC OFF-LINE TELETYPEWRITER GROUP IS A CONFIGURATION OF TELETYPEWRITER EQUIPMENT USED WITH CERTAIN CIPHER MACHINES (SEE BELOW) TO FACILITATE THE RAPID ENCIPHERING OR DECIPHERING OF TELETYPE TRAFFIC. IT IS DESIGNED PRIMARILY FOR USE ASHORE. OPERATING SPEED IS 50 WPM. THE AN/GGA-1 CONSISTS OF ONE EACH OF THE FOLLOWING ITEMS OF EQUIPMENT:						
	PP-315/G FN-30/GG SA-484/G	A-1, TAPE READER GA-1, POWER SUP IA-1, TELETYPEWE GA-1, SWITCHING NE AND HERCULES (NELATOR UNIT WHICH	PLY LITER TABLE UNIT	TT-37/GGA-1, MODEL 14 REPERFORATOR ASSOCIATED CRYPTO DEVICES: OR TT-38/GGA-1, MODEL 14 REPERFORATOR KL-34 (CSP-3000) TT-39/GGA-1, MODEL 15 PAGEPRINTER KL-47 HAVE BEEN DISCONTINUED, HOWEVER, THE KL-34 (CSP-3000) CRYPTO DEVICE IS REQUIRED FOR THE OPERATION OF THIS CONFIGURATION.			
STATUS	IN USE SPARE PARTS SUPPORT - ESO (EXCEPT TT-36 AND SA-484 WHICH ARE SUPPORTED BY CRF)						
TRAINING	A 5 WEEK COURSE IS CONDUCTED AT NORFOLK AND MARE ISLAND. BUPERS CONTROLS QUOTAS FOR NORFOLK AND EPDOPAC CONTROLS QUOTAS FOR MARE ISLAND. A SECRET CLEARANCE IS REQUIRED.						
CRYPTOSYSTEM	ADONIS/POLLUX						
CLASSIFICATION	EQUIPMENT: unclassified (confidential-crypto with associated crypto devices) KEYING MATERIAL; secret-crypto or top secret-crypto TRAFFIC; all classifications						
PUBLICATIONS	OPERATING: NONE MAINTENANCE: SHIPS 403 (APRIL 1953)						
PROCUREMENT	COMPLETED PRIOR TO 1955						
PHYSICAL CHARACTERISTICS	EQUIPMENT	HEIGHT	WIDTH	DEPTH	WEIGHT	POWER	REMARKS
	TT −3 6	13 1/4 IN.	16 1/4 IN.	20 3/4 1N.	78 LBS.		
	PP-315	15 IN.	25 1/2 IN.	9 3/4 IN.	115 LBS.	05-125 1/01	
	FN-30	26 1/2 1Na	60 3/4 IN.	25 IN.	175 LBS.	95→125 VOLTS OR 190→250 VOLTS	
	TT-37	11 1/2 IN.	17 1/2 IN.	16 1/2 IN.	77 LBS.	(60 CPS)	
	TT-38	39 1/8 IN.	21 1/2 IN.	18 IN.	167 LBS.	_	
	TT-39	42 IN.	21,1/2 IN.	18 IN.	193 LBS.	_	
	SA-484	23 IN.	22 3/4 IN.	19 IN.	80 LBS.	<u>l</u>	
DISTRIBUTION	(AFLOAT) - 9 SHIPYARDS - 11 COMMANDS - 55 WEATHER - 4 COMMSTAs - 64 OTHERS - 61 NAVSTAS - 13 SPECIAL - 30 NAVAIR - 9 MARINES - 5						





CONFIDENTIAL

2-6

CORRECTED TO 3/9/62

ORIGINAL